

FIX Hydraulic Winder

FIX Winder

(Base unit without drum)

No. 1621

Product video




- Direct drive with hydraulic engine
- The drum can be started and stopped with a lever
- Letting go of the lever stops the drum
- Can be used manually (free wheel)
- 3-point-suspension
- Rotations per min: 140
- Sturdy frame
- Dimensions: 930 x 750 x 1130 mm, 63 kg

Frame Expansion (optional)

No. 1621.1

Drip tube is uncoiled while the tractor is in motion (no assistance needed). Enables 90° rotation of the frame.



Hydraulic Speed Regulation (optional)

No. 1624

For smooth adjustment of coiling speed.

For winding wires, tacking cords and thin irrigation hoses:

Conical Steel Drum Ø 600 mm

No. 1622 (picture see base unit above)

- With tension release device
- Front disc can be easily removed to unload wire, cords, flat drippers
- With wire/cord guide

For winding and unwinding drip tubes (also first unwinding of brand new drip tubes):

Conical Steel Drum Ø 800 mm

No. 1680

- Removable aluminium discs Ø 800 mm
- Two relaxation devices
- Drum core front Ø 350 with released relaxation device
- Drum core Ø 400 with activated relaxation device
- Winding width 400 mm



Conical Steel Drum Ø 1000 mm

No. 1681

Removable aluminium discs Ø1000 mm

- Two relaxation devices
- Drum core front Ø 350 with released relaxation device
- Drum core Ø 400 with activated relaxation device
- Winding width 400 mm



For foils, nets, fleece and storage:

Plastic Drum Ø 800 mm

No. 1623

- Drum core Ø 400 mm
- Winding width 400 mm



Adapter

Adapter for Plastic Drum Ø 800 mm

No. 1628

Adapter for NETAFIM Plastic Drum Ø 570 mm

No. 1626

- Drum core Ø 140 mm
- Winding width 330 mm



Adapter for Saelens, Irritec Plastic Drum Ø 600 mm

No. 1627

- Drum core Ø 150 mm
- Winding width 350 mm



Adapters for other brands on request